

Highlights

Performance

Summit X430 series switches are based on the revolutionary ExtremeXOS that runs across all of Extreme Networks switches. Powered by ExtremeXOS, Summit X430 switches provide resilient, secure, and programmable solution for your network edge application connectivity. Summit X430 switch provides low-to-medium density PoE+ and high-density Gigabit Ethernet ports plus dedicated SFP ports in a compact 1RU format, supporting intelligent Layer 2 switching with Layer 2 - Layer 4 traffic classification and QoS on every port for predictable network performance.

Features

- 28 or 52 Gigabit Ethernet ports
- 8 port and 24 port IEEE802.3at PoE solutions
- Line rate performance on all ports.
- BASE-T connectivity to the desktop
- Dedicated BASE-X SFP ports.
- ExtremeXOS Layer 2 Edge feature set
- Limited Lifetime Warranty



Summit X430 Series

Provides Resilient, Secure, and Programmable Solution for Network Edge Application Connectivity

Overview

The Extreme Networks Summit X430 series Gigabit Ethernet standalone switches provide network edge connectivity for enterprises, branch offices, and small and medium-sized businesses. Summit X430 series are available in 28- or 52-port 10/100/1000 Mpps port models 8 or 24 port 10/100/1000 Mpps IEEE 802.3at PoE models and are ideal for network convergence of Unified Communications, wireless mobility, streaming media and multicast traffic on a single open fabric edge network.

The Summit X430 leverages a compact 1RU and 10-inch deep form factor, along with a low volume operating mode that makes it ideal for open office and wiring closet environments. Summit X430 series switches support up to 4 fixed front panel 100/1000BASE-X (SFP) unpopulated ports (two SFP ports on the 8 port PoE+ switch) that can be utilized for high-speed backbone or link aggregation connections between wiring closets.

Summit X430 series simplifies network operation by using the ExtremeXOS, a modular operating system (OS) that spans all Extreme Networks Summit and BlackDiamond Ethernet switches. Powered by ExtremeXOS, the Summit X430 series enables organizations to build highly resilient and secure edge networks that support high network uptime, simplified management, increased operational efficiency with low total cost of ownership.

The Summit X430 provides exceptional Policy-based QoS with advanced traffic management for converged applications. With eight hardware queues per port to support granular (8kbps-1Mbps) traffic classification, the Summit X430 provides flexible yet reliable solution for converged data, voice and video traffic.

Simplified Network Deployment

- Single streamlined operating system across the entire network.
- Widgets and automation scripts to simplify operation and configuration.
- LLDP/LLDP-MED to provide device management

High Performance

- High bandwidth, non-blocking architecture
- Quality of Service (QoS) with advanced traffic management capabilities.
- 8, 28 or 52 port
- Line rate ACL for controlling network resource utilization and network protection.
- Less than 5µs (64-byte) latency.

Comprehensive Security Features

- Identity aware role based policy and host integrity enforcement
- Extensive MAC and IP security functionality to help prevent man-in-the-middle attacks
- Multiple network edge authentication support with multiple endpoints per port

Scalability for Future Network Growth

- Layer 2 MAC addresses support – 16K
- Total VLANs – 4094
- Total trunks – 128 load sharing
- Maximum Layer 2 Multicast groups – 1K

Technical Specifications**

Performance

Switch Model	Bandwidth	Frame Forwarding Rate
Summit X430-8p	20 Gbps	14.8 Mpps
Summit X430-24p	56 Gbps	41.6 Mpps
Summit X430-24t	56 Gbps	41.6 Mpps
Summit X430-48t	104 Gbps	77.4 Mpps

Programmable Extensibility

- Integrate best-of-breed applications to your network with an open, yet secure XML-based Application Programming Interface (API).
- Integrate Extreme Networks and third-party developed software applications using open standards-based POSIX interfaces.

Enable Network Convergence

- Quality of Service (QoS) with advanced traffic management capabilities for converged applications.
- Traffic policing or rate limiting on ingress, 802.1Q tagging and Diffserv marking, and shaping on egress with eight queues per port provides predictable network performance.

High Availability and Resiliency

- Modular ExtremeXOS operating system
- Ethernet Automatic Protection Switching (EAPS) resiliency protocol.
- Spanning Tree (802.1D), Per VLAN Spanning Tree (PVST+), Rapid Spanning Tree (802.1w) and Multiple Instances of Spanning Tree (802.1s) protocols for Layer 2 resiliency.

Weight and Physical Dimensions

Switch Model	Weight	Physical Dimension
Summit X430-8p	5.0 lb (2.27 kg)	Height: 1RU 1.73 inches (4.4 cm) Width: 8.7 inches (22.1 cm) Depth: 10.0 inches (25.4 cm)
Summit X430-24p	10.0 lb (4.54 kg)	Height: 1RU 1.73 inches (4.4 cm) Width: 17.4 inches (44.1 cm) Depth: 10.0 inches (25.4 cm)
Summit X430-24t	8.4 lb (3.83 kg)	Height: 1RU, 1.73 inches (4.4 cm) Width: 17.4 inches (44.1 cm) Depth: 8.125 inches (20.6 cm)
Summit X430-48t	9.1 lb (4.125 kg)	Height: 1RU, 1.73 inches (4.4 cm) Width: 17.4 inches (44.1 cm) Depth: 10.0 inches (25.4 cm)

A list of supported protocols and standards is available on the Extreme Networks website at:

<http://www.extremenetworks.com/products/extreme-xos.aspx>

Technical Specifications**

Additional Performance Specifications

- Latency: <5 μ s (64 byte)
- Max Packet Size: 9KB (Jumbo Frame Support)
- Total Trunks: 128 load sharing, members per trunk: 8
- VLANs: 4, 094
- Ingress ACLs: 1,024

Forwarding Tables

- Layer 2/MAC Addresses: 16k
- Layer 2/Multicast Groups: 1k

CPU, Memory

- Single Core CPU, 500 MHz clock
- 256MB DRAM
- 256MB Compact Flash
- 1.5MB packet buffer on 8 and 24 port switches, 3.0MB packet buffer on 48 port switch

QoS, Rate Limiting

- Ingress bandwidth meters: 512
- Ingress metering granularity: 8 kbps
- Ingress bandwidth policing/rate limiting per flow/ACL
- Egress QoS queues/port: 8
- Egress bandwidth rate shaping per egress queue and per port
- Egress rate granularity: 64 kbps
- LED Indicators
- Per port status LED including power status
- System Status LEDs: management, fan and power

Operating Conditions

Temperature Range

- Humidity: 10% to 93% relative humidity, non-condensing
- Shock (Half Sine): 30m/s² (3 G), 11 ms, 60 shocks
- Random vibration: 3 to 500 Hz at 1.5 G rms

Switch Model	Temp Range	Altitude
Summit X430-8p	0° C to 40° C (32° F to 104° F)	3048 meters
Summit X430-24p	0° C to 45° C (32° F to 113° F)	2000 meters
Summit X430-24t	0° C to 45° C (32° F to 113° F)	4000 meters
Summit X430-48t	0° C to 45° C (32° F to 113° F)	3000 meters

Storage and Transportation Conditions (Packaged)

- Transportation Temperature: -40° C to 70° C (- 40° F to 158° F)
- Storage and Transportation Humidity: 10% to 95% RH
- Packaged Shock (Half Sine): 180 m/s² (18 G), 6ms, 600 shocks
- Packaged Sine Vibration: 5 – 62 Hz @ Velocity 5mm/s, 62 – 500 Hz @ 0.2 G
- Packaged Random Vibration: 5 – 20 Hz @ 1.0 ASD w/-3dB/oct. from 20 – 200 Hz 14 drops min on sides & corners @ 39.4" (<15kg box)

EMI/EMC Standards

North America EMC for ITE

- FCC CFR 47 part 15 Class A (U.S.A.)
- ICES-003 Class A (Canada)

European EMC Standards

- EN 55022:2010 Class A
- EN 61000-3-2 2006+ A2: 2008 Class A iHarmonics)
- EN 61000-3-3 2008 (Flicker)
- EN 55024 2010
- ETSI EN 300 386: v1.6.1 2008+A2:2010 (EMC Telecommunications)
- EN 61000-6-4: 2007+A1: 2011 (General Emissions for Industrial, Scientific and Medical)
- EN 61000-6-2:2005 (General Immunity for Industrial, Scientific and Medical)
- EN 50121-4:2006 (Emission and immunity of the signaling for Railway Applications)
- 2004/108/EC EMC Directive

International EMC Certifications

- CISPR 22:2010, Class A (International Emissions)
- CISPR 24 A2:2010(International Immunity) – IEC/EN 61000-4-2:2008 Electrostatic Discharge, 8kV Contact, 15kV Air, Criteria A –IEC/EN 61000-4-3:2010 Radiated Immunity 20V/m, Criteria A
- IEC/EN 61000-4-4:2012 Transient Burst – Power AC, \pm 2.0kV, Criteria A
- Power DC, \pm 2.0kV CM, 1kV DM, Criteria A – I/O Cables, \pm 2.0kV for all I/O longer than 3m
- IEC 61000-4-5:2005/EN 61000-4-5:2006 Surge

Technical Specifications**

- AC Power, 1/2kV , Criteria A, test up to 2/4kV
- DC Power 1kV DM, 2kV CM, Criteria A
- I/O 1kV L-G, Criteria A
- IEC/EN 61000-4-6:2008 Conducted Immunity, 0.15-80MHz, 10V/m unmod. RMS, Criteria A
- IEC 61000-4-8:2009/EN 61000-4-8:2010 Magnetic Immunity, Not applicable
- IEC/EN 61000-4-11:2004 Power Dips and Interruptions, >30%, 25 periods, Criteria A

International EMC Standards

- VCCI Class A (Japan Emissions)
- RCM (Australia Emissions)
- CCC Mark (China Emissions)
- KCC Mark (Korea Approval)
- GOST-E (Russia)

Telecom Standards

- ETSI EN 300 386: V1.6.1 A2:2010 EMC Telecommunications
- ETSI EN 300 018 (Environmental for Telecommunications)
- MEE 9 compliant
- MEE 14 compliant

IEEE 802.3 Media Access Standards

- IEEE 802.3ab 1000BASE-T
- IEEE 802.3z 1000BASE-X
- IEEE 802.3at PoE Plus

Environmental Standards

- EN/ETSI 300 019-2-1 v2.1.2 - Class 1.2 Storage
- EN/ETSI 300 019-2-2 v2.1.2 - Class 2.3 Transportation
- EN/ETSI 300 019-2-3 v2.1.2 - Class 3.1e Operational
- EN/ETSI 300 753 (1997-10) - Acoustic Noise
- ASTM D3580 Random Vibration Unpackaged 1.5G
- RoHS 6 compliant
- China RoHS compliant
- WEEE Compliant

Warranty

- Ltd. Lifetime with express Advanced Hardware Replacement
- For warranty details, visit:
<http://www.extremenetworks.com/go/warranty>

Safety Standards

- UL 60950-12nd Ed., Limited Devices (U.S.)
- CSA 22.2 #60950-1-03 wnd Ed. (Canada)
- Complies with FCC 21CFR1040.10 (U.S. Laser Safety)
- CDRH Letter of Approval (U.S. FDA Approval)
- EN60950-1:2006+A11+A1+A12+country deviations
- EN60825-1:2007 (Lasers Safety) TUV-RGS Mark by German Notified Body
- 2006/95/EC Low Volatage Directive
- AS/NZX 60950-1 (Australia/New Zealand)

**EXCEPT FOR THE SECTION TITLED "TECHNICAL SPECIFICATIONS" EXTREME NETWORKS MAKES NO WARRANTY WHATSOEVER WITH RESPECT TO ANY OTHER DATA CONTAINED IN THIS DATA SHEET INCLUDING ANY (A) WARRANTY OF MERCHANTABILITY; OR (B) WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE; WHETHER EXPRESS OR IMPLIED BY LAW, COURSE OF DEALING, COURSE OF PERFORMANCE, USAGE OF TRADE OR OTHERWISE.

External Ports

Switch Model	Ports
Summit X430-8p	8 x 10/100/1000Base-T PoE (RJ45) 2 x 100/1000BASE-X (SFP) unpopulated ports 1 x Serial (console port) and 1 x 10/100BASE-T out-of-band management port
Summit X430-24p	24 x 10/100/1000Base-T PoE (RJ45) 4 x 100/1000BASE-X (SFP) unpopulated ports 1 x Serial (console port) and 1 x 10/100BASE-T out-of-band management port
Summit X430-24t	24 x 10/100/1000BASE-T (RJ45) 4 x 100/1000BASE-X (SFP) unpopulated ports 1 x Serial (console port) and 1 x 10/100BASE-T out-of-band management port
Summit X430-48t	48 x 10/100/1000Base-T (RJ45) 4 x 100/1000BASE-X (SFP) unpopulated ports 1 x Serial (console port) and 1 x 10/100BASE-T out-of-band management port

Fan Acoustic Noise

Switch Model	Low Speed	High Speed
	dB(A) Sound Pressure (LpA)	dB(A) Sound Pressure (LpA)
Summit X430-8p	0 dB(A) (no fan)	0 dB(A) (no fan)
Summit X430-24t	41	49
Summit X430-24p	41	53
Summit X430-48t	38	50

Note: Sound pressure is measured in accordance with ISO 7770:2010(E).

Power Specifications

Switch Model	Switch Power	802.3at PoE Power	Total Power
Summit X430-8p	24.2W	60W Default, 90W Config Option for Standalone Operation	84.2W
Summit X430-24t	28.7W	N/A	28.7W
Summit X430-24p	55W	370W	425W
Summit X430-48t	55.9W	N/A	55.9W

Power Connections

Switch Model	Power Supply Input Socket	Power Cord Input Plug/Input Socket	Power Supply Cord Gauge	Redundant Power Supply Input Socket
Summit X430-8p	IEC 320 C14	IEC 320 C13/C14	Min 18A WG	N/A
Summit X430-24t	IEC 320 C14	IEC 320 C13/C14	Min 18A WG	N/A
Summit X430-24p	IEC 320 C14	IEC 320 C13/C14	Min 18A WG	N/A
Summit X430-48t	IEC 320 C14	IEC 320 C13/C14	Min 18A WG	N/A

Protocols and Standards

A list of supported protocols and standards is available on the Extreme Networks website at:

<http://www.extremenetworks.com/products/extreme-xos.aspx>

Ordering Information

Part Number	Name	Description
16515	Summit X430-8p	8 10/100/1000BASE-T PoE+, 2 1000BASE-X unpopulated SFP, 1 AC PSU, ExtremeXOS L2 Edge license
16516	Summit X430-24t	24 10/100/1000BASE-T, 4 1000BASE-X unpopulated SFP, 1 AC PSU, ExtremeXOS L2 Edge license
16517	Summit X430-24p	24 10/100/1000BASE-T PoE+, 4 1000BASE-X unpopulated SFP, 1 AC PSU, ExtremeXOS L2 Edge license
16518	Summit X430-48t	48 10/100/1000BASE-T, 4 1000BASE-X unpopulated SFP, 1 AC PSU, ExtremeXOS L2 Edge license.
16524	Summit X430 Multimedia (AVB) Feature Pack	ExtremeXOS Audio Video Bridging Feature Pack for Summit X430 series switches - Maximum of 100 active streams on no more than eight ports
16525	Summit X430-8p Mounting Kit	Special "Keep Out" Rack Mounting Kit for the X430-8p Switch that reserves 2RU space for adequate cooling
10051H	1000BASE-SX SFP, Hi	1000BASE-SX SFP, MMF 220 & 550 meters, LC Connector, Industrial Temp
10052H	1000BASE-LX SFP, Hi	1000BASE-LX SFP, LC Connector, Industrial Temp
10053H	1000BASE-ZX SFP, Hi	1000BASE-ZX SFP, SMF 70 km, LC Connector, Industrial Temp
10056H	1000BASE-BX-D SFP, Hi	1000BASE-BX-D SFP, SMF (1490nm TX/1310nm RX Wavelength), Industrial Temp
10057H	1000BASE-BX-U SFP, Hi	1000BASE-BX-U SFP, SMF (1310nm TX/1490nm RX Wavelength), Industrial Temp
10060	100FX/1000LX SFP	100FX/1000LX SFP, SMF, LC Connector (Requires MCP and 6dB Attenuator for 100FX-MMF Operation)
10063	100FX SFP	100FX SFP, MMF, LC Connector
10064	1000BASE-LX100 SFP	1000BASE-LX100 SFP, Extra Long Distance SMF 100 km/30dB Budget, LC Connector
10065	10/100/1000Base-T SFP	10/100/1000BASE-T SFP module, Category 5 cable 100m link, RJ45-Connector
10067	100BASE-FX SFP	100M SFP, 100FX MMF, (1310nm, 2km multimode transmission) LC connector
10066	100BASE-LX10 SFP	100M SFP, 100LX10 SMF, (1310nm 10km single mode transmission) LC connector
10058	100BASE-BX-D SFP	100M SFP, 100BASE-BX-D, SMF (1550nm TX/1310nm RX wavelength), 100 Mbps
10059	100BASE-BX-U SFP	100M SFP, 100BASE-BX-U, SMF (1310nm TX/1550nm RX wavelength), 100 Mbps bidirectional
10071H	1000BASE-SX SFP 10 Pack, Hi	1000BASE-SX SFP 10 Pack, Industrial Temp
10072H	1000BASE-LX SFP 10 Pack, Hi	1000BASE-LX SFP 10 Pack, Industrial Temp

Power Cords

In support of the Extreme Networks Green initiatives, power cords can be ordered separately but need to be specified at the time order. Please refer to www.extremenetworks.com/product/powercords/ for details on power cord availability for this product..



<http://www.extremenetworks.com/contact> / Phone +1-408-579-2800

©2018 Extreme Networks, Inc. All rights reserved. Extreme Networks and the Extreme Networks logo are trademarks or registered trademarks of Extreme Networks, Inc. in the United States and/or other countries. All other names are the property of their respective owners. For additional information on Extreme Networks Trademarks please see <http://www.extremenetworks.com/company/legal/trademarks>. Specifications and product availability are subject to change without notice. 1906-0417-25